

MMX6000 Sloped Top Stainless Steel Enclosure



Quick Connect Breakout



Easy-To-Remove Base Plate



Product Features

Take multiple measurements from one location

Safe, centralized data collection point, with a sloped top to prevent dirt and dust build-up. Modular units can easily be installed or removed with the Quick-Release DIN rail clip

- Connects up to 9 remotely installed sensors to portable data collectors, providing a safe data collection point
- Buy the modules that you need now, add more in the future
- Removable bottom base plate allows for easy installation of user defined inputs
- Switch provided to tie common (-) signals for dual or triaxial sensors

Specifications

MMX6000	
Inputs	Terminal Block 3 Inputs per channel (+,-, Shield)
Output	BNC Jack Per Channel, Electrically Isolated
Conduit Fittings (For Rigid Body Conduit)	3/4" = 3 Channels 1" = 6 & 9 Channels
Cord Grip	0.118 – 0.256 inches (3,0 – 6,5 mm)
Rating	NEMA 4X (IP66)
Door Closure	Twist Lock
Material	Stainless Steel
Temperature Rating	-58° to 180° F (-50° to 82° C)
Resistance	Resistant to Hose Directed Fluid and Corrosion

Ordering Information

MMX -

Enclosure Type
6000 = Stainless Steel Enclosure with Sloped Top

Channels
3 = 3 Channels
6 = 6 Channels
9 = 9 Channels

Input Options
A = *User Defined 
B = **Conduit Fitting 
C = Cord Grips 
S = †Stainless Steel Cord Grips 

Example Part Number: MMX6000-3A

Stainless steel Modular MAXX Box with sloped top and one (3 channels) din rail mounted BNC module

* No punch outs are provided in the enclosure for cable entry. User may install any fitting required.

** For use with rigid body conduit.

† Stainless Steel enclosure only.