

Armor & Hydraulic Hose Protected Cabling

Section 2 - Cables & Connectors

Part No.	Jacket Material	Use	Conductor Qty.	Shielding Method	Max Temp.	Cable Diameter Weight/Ft.	Wire Gauge	Ratings/Certifications
CB202	Red Teflon® with Stainless Steel Armor Cover	Permanent Monitoring	2 Conductor	Foil with Drain Wire	400°F (204°C)	.270 in (6,9 mm), .175 in (4,5 mm) 1.0 lbs./20 ft.	AWG = 20	 RoHS
 <p>Compatible Connectors: A2A, A2E, A2P, A2R, A2S, A2V, A2Y, B2A, B2N, B2R, D2H, D2J, E, EMPP, EX, F, FHD, FX, FX90, J2A, J2P, L, R2C, Z</p> <p>Maximum Armor Length: 20 ft (6 m)</p>								
CB206	Red Teflon® with Stainless Steel Armor Cover	Permanent Mount	2 Conductor	Foil with Drain Wire	400°F (204°C)	.270 in (6,9 mm), .118 in (3 mm) 4.4 lbs./100 ft.	AWG = 22	 RoHS
 <p>Compatible Connectors: A2A, A2E, A2N, A2P, A2R, A2S, A2U, A2V, A2Y, B2A, B2N, B2R, D2H, D2J, E, EMPP, EX, F, FHD, FX, FX90, J2A, J2P, R2C, L, Z</p> <p>Maximum Armor Length: 100 ft (30 m)</p>								
CB212	White Teflon® with Stainless Steel Armor Cover	Permanent Mount	3 Conductor	Foil with Drain Wire	400°F (204°C)	.270 in (6,9 mm), .175 in (4,5 mm) 1.0 lbs./20 ft.	AWG = 20	 RoHS
 <p>Compatible Connectors: A3A, A3E, A3N, A3P, A3R, A3S, A3U, A3V, A3Y, B3A, B3R, E2C, F2C, L, Z</p> <p>Maximum Armor Length: 20 ft (6 m)</p>								
CB218	Red Teflon® with Stainless Steel Armor Cover	Permanent Mount	4 Conductor	Foil with Drain Wire	400°F (204°C)	.270 in (6,9 mm), .148 in (3,8 mm) 5.1 lbs./100 ft.	AWG = 20	 RoHS
 <p>Compatible Connectors: A3A, A3E, A3N, A3R, A3S, A3V, A3Y, B3A, B3N, B3R, D3H,E2C, E3C, F2C, F3C, G3H, G4H1, L, Z</p> <p>Maximum Armor Length: 100 ft (30 m)</p>								
CB502	Red Teflon® with Hydraulic Hose Cover	Permanent Mount	2 Conductor	Foil with Drain Wire	212°F (100°C)	.500 in (12,7 mm), .175 in (4,5 mm) 2.0 lbs./20 ft.	AWG = 22	RoHS
 <p>Compatible Connectors: A2L, D2M, L, Z</p> <p>Maximum Hose Length: 20 ft (6 m)</p>								
CB511	Yellow Teflon® with Hydraulic Hose Cover	Permanent Mount	2 Conductor	Braided Shield with Drain Wire	212°F (100°C)	.500 in (12,7 mm), .190 in (4,8 mm) 2.0 lbs./20 ft.	AWG = 20	RoHS
 <p>Compatible Connectors: A2L, D2M, L, Z</p> <p>Maximum Hose Length: 20 ft (6 m)</p>								
CB512	White Teflon® with Hydraulic Hose Cover	Permanent Mount	3 Conductor	Foil with Drain Wire	212°F (100°C)	.500 in (12,7 mm), .175 in (4,5 mm) 2.1 lbs./20 ft.	AWG = 20	RoHS
 <p>Compatible Connectors: A3L, D3M, L, Z</p> <p>Maximum Hose Length: 20 ft (6 m)</p>								

* Teflon® is a registered trademark of DuPont.