




















Armor & Hydraulic Hose Protected Cabling

Part No.	Jacket Material	Use	Conductor Qty.	Shielding Method	Max Temp.	Cable Diameter Weight/Ft.	Wire Gauge	Ratings/Certifications
CB802		Permanent Monitoring	2 Conductor	Foil with Drain Wire	400°F (204°C)	.250 in (6,4 mm), .175 in (4,5 mm) 1.5 lbs./30 ft.	AWG = 20	  RoHS
CB806		Permanent Monitoring	2 Conductor	Foil with Drain Wire	400°F (204°C)	.250 in (6,4 mm), .118 in (4,5 mm) 4.0 lbs./100 ft.	AWG = 20	  RoHS
CB810		Permanent Monitoring	2 Conductor	Braided Shield with Drain Wire	250°F (121°C)	.250 in (6,4 mm), .175 in (4,5 mm) 1.6 lbs./25 ft.	AWG = 20	 RoHS
CB811		Permanent Monitoring	2 Conductor	Braided Shield with Drain Wire	400°F (204°C)	.250 in (6,4 mm), .190 in (4,8 mm) 1.6 lbs./25 ft.	AWG = 20	  RoHS
CB812		Permanent Monitoring	3 Conductor	Foil with Drain Wire	400°F (204°C)	.250 in (6,4 mm), .190 in (4,8 mm) 1.7 lbs./25 ft.	AWG = 20	  RoHS
CB818		Permanent Monitoring	4 Conductor	Foil with Drain Wire	400°F (204°C)	.250 in (6,4 mm), .148 in (3,8 mm) 5.1 lbs./100 ft.	AWG = 22	 RoHS
CB819		Permanent Monitoring	4 Conductor	Foil with Drain Wire	400°F (204°C)	.250 in (6,4 mm), .190 in (4,8 mm) 1.4 lbs./25 ft.	AWG = 22	  RoHS

* Teflon® is a registered trademark of DuPont.