



















# Cabling

Part No.	Jacket Material	Use	Conductor Qty.	Shielding Method	Max Temp.	Cable Diameter Weight/Ft.	Wire Gauge	Ratings/Certifications
<b>CB112</b>	White Teflon® 	Permanent Monitoring	3 Conductor	Foil with Drain Wire	400°F (204°C)	.175 in (4,5 mm) 29.7 lbs./1000 ft.	AWG = 20	 RoHS PLENUM 
<b>CB105</b>	Black Polyurethane 	Permanent Monitoring / Portable Measurement	4 Conductor	Braided Shield with Drain Wire	250°F (121°C)	.250 in (6,4 mm) 49.0 lbs./1000 ft.	AWG = 20	 RoHS
<b>CB117</b>	Black Polyurethane, Coiled 	Portable Measurement	4 Conductor	Braided Shield	250°F (121°C)	.210 in (5,3 mm) 0.50 lbs./10 ft.	AWG = 25	 RoHS
<b>CB119</b>	Orange Teflon® 	Permanent Monitoring	4 Conductor	Foil with Drain Wire	400°F (204°C)	.190 in (4,8 mm) 35.4 lbs./1000 ft.	AWG = 22	 RoHS 
<b>CB123</b>	Slate Polyurethane 	Permanent Monitoring	6 Conductor	Braided Shield with Drain Wire	250°F (121°C)	.250 in (6,4 mm) 39.3 lbs./1000 ft.	AWG = 20	RoHS
<b>CB115</b>	Black PVC 	Permanent Monitoring	8 Pair Multi Conductor	Foil with Drain Wire (each pair)	221°F (105°C)	.51 in (12,9 mm) 184.0 lbs./1000 ft.	AWG = 20	 RoHS
<b>CB109</b>	Black PVC 	Permanent Monitoring	12 Pair Multi Conductor	Foil with Drain Wire (each pair)	221°F (105°C)	.64 in (16,2 mm) 274.0 lbs./1000 ft.	AWG = 20	 RoHS
<b>CB114</b>	Black PVC 	Permanent Monitoring	16 Pair Multi Conductor	Foil with Drain Wire (each pair)	221°F (105°C)	.70 in (17,7 mm) 402.0 lbs./1000 ft.	AWG = 20	 RoHS
<b>CB122</b>	Black TPE 	Permanent Monitoring	12 Pair Multi Conductor	Foil with Drain Wire (each pair)	250°F (121°C)	.64 in (16,2 mm) 267.0 lbs./1000 ft.	AWG = 20	RoHS

\* Teflon® is a registered trademark of DuPont.

Note: Bulk cable purchase discount is available for cable purchased in 1000 ft. reels