

# Factory Installed Cable Connectors

**A2R**  
2 Socket, MIL-Style  
**Polyphenylene Sulfide (PPS) Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Signal (-)	392° F (200° C)	CB102, CB103, CB110, CB111, CB206, CB802, CB806, CB810, CB811

IP66 Build To Order

**A3R**  
3 Socket, MIL-Style  
**Polyphenylene Sulfide (PPS) Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Signal (-) C = Signal (+) White	392° F (200° C)	CB105, CB112, CB212, CB218, CB812, CB818

IP66 Build To Order

**A2S**  
2 Socket, MIL-Style  
**Polyphenylene Sulfide (PPS) Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Signal (-)	392° F (200° C)	CB102, CB111, CB202, CB206, CB802, CB806, CB810, CB811

IP66 Build To Order

**A3S**  
3 Socket, MIL-Style  
**Polyphenylene Sulfide (PPS) Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Signal (-) C = Signal (+) White	392° F (200° C)	CB112, CB212, CB218, CB812, CB818

IP66 Build To Order

**A2U**  
2 Socket, Right Angle MIL-Style  
**Polyurethane Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Common (-)	250° F (121° C)	CB102, CB103, CB110, CB111, CB206

IP66 Build To Order

**A3U**  
3 Socket, Right Angle MIL-Style  
**Polyurethane Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Common (-) C = Signal (+) White	250° F (121° C)	CB105, CB112, CB212, CB218, CB812, CB818

IP66 Build To Order

**A2V**  
2 Socket, Right Angle MIL-Style  
**Polyphenylene Sulfide (PPS) Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Signal (-)	392° F (200° C)	CB102, CB103, CB110, CB111, CB202, CB206, CB802, CB806, CB810, CB811

IP66 Build To Order

**A3V**  
3 Socket, Right Angle MIL-Style  
**Polyphenylene Sulfide (PPS) Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Signal (-) C = Signal (+) White	392° F (200° C)	CB105, CB112, CB212, CB218, CB812, CB818

IP66 Build To Order

**A2Y**  
2 Socket, Right Angle MIL-Style  
**Nylon Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Common (-)	250° F (121° C)	CB102, CB103, CB110, CB111, CB202, CB206

IP66 Build To Order

**A3Y**  
3 Socket, Right Angle MIL-Style  
**Nylon Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	A = Signal (+) B = Common (-) C = Signal (+) White	250° F (121° C)	CB105, CB112, CB212, CB218

IP66 Build To Order



Backed by our Unconditional Lifetime Warranty