

# Factory Installed Cable Connectors

Section 2 - Cables & Connectors

**E**  
**BNC Jack, Molded**  
**Poly-carbonate Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB104, CB108, CB110, CB111, CB202, CB206

IP66

Build To Order

**EX**  
**BNC Jack**  
**Epoxyed**

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB104, CB108, CB110, CB111, CB202, CB206

IP66

Build To Order

**E3C**  
**3 BNC Jacks to 1 Multi-Conductor Cable**  
**Polycarbonate Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

\* Complete Technical Drawing Available on Page 137

Build To Order

**F**  
**BNC Plug**  
**Polycarbonate Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB104, CB108, CB110, CB111, CB202, CB206

IP66

Build To Order

**F2C**  
**2 BNC Plugs to 1 Multi-Conductor Cable**  
**Polycarbonate Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

\* Complete Technical Drawing Available on Page 137

Build To Order

**EMPP**  
**BNC Measurement Point with Protector**  
**Nylon Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB110, CB111, CB202, CB206, CB802, CB806, CB810, CB811

IP66

Protector helps shield connector from environmental hazards

Build To Order

**E2C**  
**2 BNC Jacks to 1 Multi-Conductor Cable**  
**Polycarbonate Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

\* Complete Technical Drawing Available on Page 137

Build To Order

**E4C**  
**4 BNC Jacks to 1 Multi-Conductor Cable**  
**Polycarbonate Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

\* Complete Technical Drawing Available on Page 137

Build To Order

**FX**  
**BNC Plug**  
**Epoxyed**

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB104, CB108, CB110, CB111, CB202, CB206

IP66

Build To Order

**F3C**  
**3 BNC Plugs to 1 Multi-Conductor Cable**  
**Polycarbonate Molded**

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

\* Complete Technical Drawing Available on Page 137

Build To Order

