

Factory Installed Cable Connectors

Section 2 - Cables & Connectors

E
BNC Jack, Molded
Poly-carbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB104, CB108, CB110, CB111, CB202, CB206

IP66

Build To Order

EX
BNC Jack
Epoxyed

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB104, CB108, CB110, CB111, CB202, CB206

IP66

Build To Order

E3C
3 BNC Jacks to 1 Multi-Conductor Cable
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

* Complete Technical Drawing Available on Page 137

Build To Order

F
BNC Plug
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB104, CB108, CB110, CB111, CB202, CB206

IP66

Build To Order

F2C
2 BNC Plugs to 1 Multi-Conductor Cable
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

* Complete Technical Drawing Available on Page 137

Build To Order

EMPP
BNC Measurement Point with Protector
Nylon Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB110, CB111, CB202, CB206, CB802, CB806, CB810, CB811

IP66

Protector helps shield connector from environmental hazards

Build To Order

E2C
2 BNC Jacks to 1 Multi-Conductor Cable
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

* Complete Technical Drawing Available on Page 137

IP66

Build To Order

E4C
4 BNC Jacks to 1 Multi-Conductor Cable
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

* Complete Technical Drawing Available on Page 137

Build To Order

FX
BNC Plug
Epoxyed

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements, Permanent Mount	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB102, CB103, CB104, CB108, CB110, CB111, CB202, CB206

IP66

Build To Order

F3C
3 BNC Plugs to 1 Multi-Conductor Cable
Polycarbonate Molded

Application	Pin Out	Max. Temp.	Compatible Cables
Portable Measurements	Pin = Signal (+) Case = Common (-)	250° F (121° C)	CB105, CB117, CB119

* Complete Technical Drawing Available on Page 137

Build To Order

