





















Connector Kits for Field Installation

Part #	Installed Connector Side View	Connector Kit Parts	Connector Kit Parts #	Diameter	Max Temp.	Compatible Cables
CC-A2A-175 CC-A2A-190 CC-A2A-250 CC-A2A-360		 <p>2 Socket MIL-Style Connector Kit</p>	CC-A2A-175	.175" (4,5 mm)	250°F (121°C)	CB102, CB110
			CC-A2A-190	.190" (4,8 mm)	250°F (121°C)	CB111
			CC-A2A-250	.250" (6,4 mm)	250°F (121°C)	CB103
			CC-A2A-360	.360" (9,1 mm)	250°F (121°C)	CB206
CC-A2N		 <p>2 Socket MIL-Style Connector Kit, High Temperature</p>	CC-A2N	.310" (7,8 mm)	250°F (121°C)	CB102, CB103, CB110, CB111, CB206
CC-A2R		 <p>2 Socket MIL-Style Connector Kit, High Temperature</p>	CC-A2R	.375" (9,5 mm)	392°F (200°C)	CB102, CB111
CC-A2S		 <p>2 Socket MIL-Style Connector Kit, Sulfuric Acid</p>	CC-A2S	.375" (9,5 mm)	392°F (200°C)	CB102, CB111
CC-A3A-175 CC-A3A-190 CC-A3A-250 CC-A3A-360		 <p>3 Socket MIL-Style Connector Kit</p>	CC-A3A-175	.175" (4,5 mm)	250°F (121°C)	CB112
			CC-A3A-190	.190" (4,8 mm)	250°F (121°C)	CB117
			CC-A3A-250	.250" (6,4 mm)	250°F (121°C)	CB105, CB218
			CC-A3A-360	.360" (9,1 mm)	250°F (121°C)	CB218
CC-A3N		 <p>3 Socket MIL-Style Connector Kit, High Temperature</p>	CC-A3N	.310" (7,8 mm)	250°F (121°C)	CB105, CB112 CB218
CC-A3R		 <p>3 Socket MIL-Style Connector Kit</p>	CC-A3R	.375" (9,5 mm)	392°F (200°C)	CB112, CB218
CC-A3S		 <p>3 Socket MIL-Style Connector Kit</p>	CC-A3S	.375" (9,5 mm)	392°F (200°C)	CB112
CC-B2A-175 CC-B2A-190 CC-B2A-250		 <p>2 Socket Seal Tight Boot Connector Kit</p>	CC-B2A-175	.175" (4,5 mm)	250°F (121°C)	CB102, CB110
			CC-B2A-190	.190" (4,8 mm)	250°F (121°C)	CB111
			CC-B2A-250	.250" (6,4 mm)	250°F (121°C)	CB103, CB206
CC-B2R-175 CC-B2R-190 CC-B2R-250		 <p>2 Socket Seal Tight Boot Connector Kit, High Temperature</p>	CC-B2R-175	.175" (4,5 mm)	392°F (200°C)	CB102
			CC-B2R-190	.190" (4,8 mm)	392°F (200°C)	CB111
			CC-B2R-250	.250" (6,4 mm)	392°F (200°C)	CB206