



















# Connector Kits for Field Installation

Part #	Installed Connector Side View	Connector Kit Parts	Connector Kit Parts #	Diameter	Max Temp.	Compatible Cables
<b>CC-A2N</b>	 <b>Stock Product</b>	 2 Socket MIL-Style Connector Kit, High Temperature	<b>CC-A2N</b>	.310" (7,8 mm)	250°F (121°C)	CB102, CB103, CB110, CB111, CB206
Supplied with epoxy and syringe (MH109-3A)						
<b>CC-A2R</b>	 <b>Stock Product</b>	 2 Socket MIL-Style Connector Kit, High Temperature	<b>CC-A2R</b>	.375" (9,5 mm)	392°F (200°C)	CB102, CB111
Supplied with epoxy and syringe (MH109-3A)						
<b>CC-A2S</b>	 <b>Stock Product</b>	 2 Socket MIL-Style Connector Kit, Sulfuric Acid	<b>CC-A2S</b>	.375" (9,5 mm)	392°F (200°C)	CB102, CB111
Supplied with epoxy and syringe (MH109-3A)						
<b>CC-A3A-175</b> <b>CC-A3A-190</b> <b>CC-A3A-250</b> <b>CC-A3A-360</b>	 <b>Stock Product</b>	 3 Socket MIL-Style Connector Kit	<b>CC-A3A-175</b> <b>CC-A3A-190</b> <b>CC-A3A-250</b> <b>CC-A3A-360</b>	.175" (4,5 mm) .190" (4,8 mm) .250" (6,4 mm) .360" (9,1 mm)	250°F (121°C) 250°F (121°C) 250°F (121°C) 250°F (121°C)	CB112 CB117 CB105, CB218 CB218
Supplied with epoxy and syringe (MH109-3A)						
<b>CC-A3N</b>	 <b>Stock Product</b>	 3 Socket MIL-Style Connector Kit, High Temperature	<b>CC-A3N</b>	.310" (7,8 mm)	250°F (121°C)	CB105, CB112 CB218
Supplied with epoxy and syringe (MH109-3A)						
<b>CC-A3R</b>	 <b>Stock Product</b>	 3 Socket MIL-Style Connector Kit	<b>CC-A3R</b>	.375" (9,5 mm)	392°F (200°C)	CB112, CB218
Supplied with epoxy and syringe (MH109-3A)						
<b>CC-A3S</b>	 <b>Stock Product</b>	 3 Socket MIL-Style Connector Kit	<b>CC-A3S</b>	.375" (9,5 mm)	392°F (200°C)	CB112
Supplied with epoxy and syringe (MH109-3A)						
<b>CC-B2A-175</b> <b>CC-B2A-190</b> <b>CC-B2A-250</b>	 <b>Stock Product</b>	 2 Socket Seal Tight Boot Connector Kit	<b>CC-B2A-175</b> <b>CC-B2A-190</b> <b>CC-B2A-250</b>	.175" (4,5 mm) .190" (4,8 mm) .250" (6,4 mm)	250°F (121°C) 250°F (121°C) 250°F (121°C)	CB102, CB110 CB111 CB103, CB206
Supplied with epoxy and syringe (MH109-3A)						
<b>CC-B2R-175</b> <b>CC-B2R-190</b> <b>CC-B2R-250</b>	 <b>Stock Product</b>	 2 Socket Seal Tight Boot Connector Kit, High Temperature	<b>CC-B2R-175</b> <b>CC-B2R-190</b> <b>CC-B2R-250</b>	.175" (4,5 mm) .190" (4,8 mm) .250" (6,4 mm)	392°F (200°C) 392°F (200°C) 392°F (200°C)	CB102 CB111 CB206
Supplied with epoxy and syringe (MH109-3A)						

