












Connector Kits for Field Installation

SECTION 2 - CABLES & CONNECTORS
Connector Kits for Field Installation

Part #	Installed Connector Side View	Connector Kit Parts	Connector Kit Parts #	Diameter	Max Temp.	Compatible Cables
CC-B3R-175 CC-B3R-190 CC-B3R-250 Supplied with epoxy and syringe (MH109-3A)		 3 Socket Seal Tight Boot Connector Kit	CC-B3R-175	.175" (4,5 mm)	392°F (200°C)	CB112
			CC-B3R-190	.190" (4,8 mm)	392°F (200°C)	
			CC-B3R-250	.250" (6,4 mm)	392°F (200°C)	CB212, CB218
CF-C1		 7 Pin ENTEK / DATALINE Connector Kit	CF-C1	≤.250" (6,4 mm)	250°F (121°C)	CB103, CB104 CB108, CB117
CC-C2X		 2 Socket MIL-Style Connector Kit	CC-C2X	.250" (6,4 mm)	250°F (121°C)	All 2 Conductor CTC Cables
CF-C3 (CSI) CF-C4 (SKF)		 25 Pin Connector Kit for use with CSI & SKF Data Collectors	CF-C3	≤.250" (6,4 mm)	250°F (121°C)	CB103, CB104 CB105, CB108, CB117, CB218
CF-C4 (SKF)		 25 Pin Connector Kit for use with CSI & SKF Data Collectors	CF-C4	≤.250" (6,4 mm)	250°F (121°C)	CB103, CB104 CB105, CB108, CB117, CB218
CC-C3X		 3 Socket MIL-Style Connector Kit	CC-C3X	≤.250" (6,4 mm)	250°F (121°C)	CB105, CB112 CB117, CB212, CB218
CF-D2C-175 CF-D2C-210 CF-D2C-250 Supplied with epoxy and syringe (MH109-3A)		 2 Socket MIL Connector Kit	CF-D2C-175	.175" (4,5 mm)	250°F (121°C)	CB102, CB110
			CF-D2C-210	.210" (5,3 mm)	250°F (121°C)	CB104
			CF-D2C-250	.250" (6,4 mm)	250°F (121°C)	CB103, CB206
CF-D3C-175 CF-D3C-250 Supplied with epoxy and syringe (MH109-3A)		 3 Socket MIL Connector Kit	CF-D3C-175	.175" (4,5 mm)	250°F (121°C)	CB112
			CF-D3C-250	.250" (6,4 mm)	250°F (121°C)	CB105, CB117
CF-D2D-250		 2 Socket, Right Angle Connector Kit	CF-D2D-250	≤.250" (6,4 mm)	250°F (121°C)	CB102, CB103, CB104, CB108 CB110, CB111
CF-D2H-250		 2 Socket MIL Connector Kit	CF-D2H-250	.250" (6,4 mm)	250°F (121°C)	All 2 Conductor CTC Cables
CF-D2J-250		 2 Socket, High Temp Connector Kit	CF-D2J-250	≤.250" (6,4 mm)	350°F (177°C)	CB102, CB206, CB111

Backed by our Unconditional Lifetime Warranty

