

ThermoPro™ TP8 & TP8S

Top-end IR Thermographic Camera




TP8S



TP8

Improved on the most advanced IR package available now, integrating multiple technologies never used in the industry, ThermoPro™ TP8 & TP8S are another ingenious solution Guide IR provides for professional IR thermographers around the world. In a rugged, compact and durable magnesium casing, ThermoPro™ TP8 & TP8S offer a wide assortment of unexpected features that enable thermographers to work with unprecedented efficiency and productivity. Exceeding all the existing IR radiometric cameras, it sets another new standard of the first-class products for the whole industry.



Applications

- Predictive and preventative maintenance
- Electricity inspections
- Building diagnostics
- Technical diagnostics
- Veterinarian helper
- Portable law enforcement

Features and Benefits

- New-generation high-performance IR detector
- Intuitive detachable touch screen & remote control handle
- High thermal sensitivity and precise temperature measurement
- High-resolution image presentation
- Real-time radiometric recording and JPEG image storage
- High-speed data transfer via USB2.0
- Synchronous video output on VGA LCD screen
 - OLED viewfinder, VGA display device & TV display device
- Ultra-large-capacity 2GB SD memory card
- Compact architecture and intuitive touch screen control
- Robust post-processing software
- License free and rapid delivery

	TP8	TP8S
Imaging Performance		
Detector Type	Microbolometer UFPA 384 × 288 pixels, 25 μ m	
Spectral Range	8-14 μ m	
Thermal Sensitivity	≤ 0.08° C at 30° C	
Field of View/ Focus	15.6° × 11.7° / 35mm	
Image Presentation		
External Display	3.5" high resolution color VGA LCD, 640 × 480 pixels	
Image Display	Thermal image alone/ Visual image alone/ Picture in picture/Image fusion	
Measurement		
Temperature Range	-20 °C - +800 °C (up to +2000 °C optional)	-20 °C - +600 °C (up to +2000 °C optional)
Accuracy	± 2° or ± 2% of reading;	
Measurement Modes	Auto hot/cold spot , auto alarm for temperature above or below ; spots, areas displaying either max, min, or average, vertical & horizontal line profile, delta-t, histogram & isotherm in live/zoomed/frozen/saved image & video	
Image Storage		
Type	Removable 2GB SD card or built-in flash memory	
Voice Annotation	Up to 60 seconds per file	
Laser Locator		
Classification Type	Class 2 semiconductor laser	
Power System		
Battery Type	Rechargeable Li-ion Camcorder battery, field- replaceable	
Battery Operating Time	Over 2.5 hours continuous operation	
Environmental Specification		
Operating Temperature	-20 °C ~ +60 °C (-40 °C ~ +70 °C optional)	
Storage Temperature	-20 °C ~ +60 °C (-40 °C ~ +70 °C optional)	
Interfaces		
USB 2.0	Image and real-time video transfer to PC; Real-time control of the camera on PC;	Image transfer to PC
Physical Characteristics		
Weight	1.1kg (including battery & LCD)	
Size	186mm × 106mm × 83mm (standard model)	