

Armor & Hydraulic Hose Protected Cabling

Part No.	Jacket Material	Use	Conductor Qty.	Shielding Method	Max Temp.	Cable Diameter Weight/Ft.	Wire Gauge	Ratings/Certifications
CB202 	Red Teflon® with Stainless Steel Armor Cover	Permanent Monitoring	2 Conductor	Foil with Drain Wire	400°F (204°C)	.270 in (6,9 mm), .175 in (4,5 mm) 1.0 lbs./20 ft.	AWG = 20	RoHS 
			Compatible Connectors: A2A, A2E, A2N, A2P, A2R, A2S, A2U, A2V, A2Y, B2A, B2N, B2R, D2H, D2J, E, EMPP, EX, F, FX, FX90, J2A, J2N, J2P, R2C, L, Z			Maximum Armor Length: 20 ft (6 m)		
CB206 	Red Teflon® with Stainless Steel Armor Cover	Permanent Mount	2 Conductor	Foil with Drain Wire	400°F (204°C)	.270 in (6,9 mm), .118 in (3 mm) 4.4 lbs./100 ft.	AWG = 22	RoHS 
			Compatible Connectors: A2A, A2E, A2N, A2P, A2R, A2S, A2U, A2V, A2Y, B2A, B2N, B2R, D2H, D2J, E, EMPP, EX, F, FX, FX90, J2A, J2N, J2P, R2C, L, Z			Maximum Armor Length: 100 ft (30 m)		
CB212 	White Teflon® with Stainless Steel Armor Cover	Permanent Mount	3 Conductor	Foil with Drain Wire	400°F (204°C)	.270 in (6,9 mm), .175 in (4,5 mm) 1.0 lbs./20 ft.	AWG = 20	RoHS 
			Compatible Connectors: A3A, A3E, A3N, A3P, A3R, A3S, A3U, A3V, A3Y, B3A, B3R, E2C, F2C, L, Z			Maximum Armor Length: 20 ft (6 m)		
CB218 	Red Teflon® with Stainless Steel Armor Cover	Permanent Mount	4 Conductor	Foil with Drain Wire	400°F (204°C)	.270 in (6,9 mm), .148 in (3,8 mm) 5.1 lbs./100 ft.	AWG = 22	RoHS 
			Compatible Connectors: A3A, A3E, A3N, A3R, A3S, A3V, A3Y, B3A, B3N, B3R, D3H, E2C, E3C, F2C, F3C, G3H, G4H1, L, Z			Maximum Armor Length: 100 ft (30 m)		
CB502 	Red Teflon® with Hydraulic Hose Cover	Permanent Mount	2 Conductor	Foil with Drain Wire	212°F (100°C)	.500 in (12,7 mm), .175 in (4,5 mm) 2.0 lbs./20 ft.	AWG = 22	RoHS
			Compatible Connectors: A2L, D2M, L, Z			Maximum Hose Length: 20 ft (6 m)		
CB511 	Yellow Teflon® with Hydraulic Hose Cover	Permanent Mount	2 Conductor	Braided Shield with Drain Wire	212°F (100°C)	.500 in (12,7 mm), .190 in (4,8 mm) 2.0 lbs./20 ft.	AWG = 20	RoHS
			Compatible Connectors: A2L, D2M, L, Z			Maximum Hose Length: 20 ft (6 m)		
CB512 	White Teflon® with Hydraulic Hose Cover	Permanent Mount	3 Conductor	Foil with Drain Wire	212°F (100°C)	.500 in (12,7 mm), .175 in (4,5 mm) 2.1 lbs./20 ft.	AWG = 20	RoHS
			Compatible Connectors: A3L, D3M, L, Z			Maximum Hose Length: 20 ft (6 m)		
CB602 	Red Teflon® with Heavy Duty Stainless Steel Armor Cover	Permanent Mount	2 Conductor	Foil with Drain Wire	400°F (204°C)	.303 in (7,7 mm), .175 in (4,5 mm) 4.1 lbs./100 ft.	AWG = 20	RoHS 
			Compatible Connectors: A2A, A2E, A2RX, J2AX, J2NX, L, Z			Maximum Armor Length: 100 ft (30 m)		
CB606 	Red Teflon® with Heavy Duty Stainless Steel Armor Cover	Permanent Mount	2 Conductor	Foil with Drain Wire	400°F (204°C)	.303 in (7,7 mm), .118 in (3 mm) 4.9 lbs./200 ft.	AWG = 22	RoHS 
			Compatible Connectors: A2A, A2E, A2RX, J2AX, J2NX, L, Z			Maximum Armor Length: 200 ft (61 m)		
CB612 	White Teflon® with Heavy Duty Stainless Steel Armor Cover	Permanent Mount	3 Conductor	Foil with Drain Wire	400°F (204°C)	.303 in (7,7 mm), .175 in (4,5 mm) 4.5 lbs./100 ft.	AWG = 20	RoHS 
			Compatible Connectors: A3A, A3E, A3RX, L, Z			Maximum Armor Length: 100 ft (30 m)		
CB618 	Red Teflon® with Heavy Duty Stainless Steel Armor Cover	Permanent Mount	4 Conductor	Foil with Drain Wire	400°F (204°C)	.303 in (7,7 mm), .148 in (3,8 mm) 12.6 lbs./200 ft.	AWG = 22	RoHS 
			Compatible Connectors: J4AX, J4NX, L, Z			Maximum Armor Length: 200 ft (61 m)		

* Teflon® is a registered trademark of DuPont.